



<h1>TYPE [D-01]</h1> <h2>GENERAL 2.1</h2>	
<p>General Standard Height office door.</p>	
FRAME [D-01]	DOOR [D-01]
PLAN VIEW [D-01]	
DESCRIPTION 'D-01'	
<p>FRAME: 855mm wide x 2066mm high Aluminium door frame with 20mm wide frame edge and 10mm closer section to suit 90mm thick dry-walling system. Clear open section for door leaf = 815mm wide x 2046mm high.</p> <p>DOOR: Flush 813mm wide x 2032mm high Masonite honeycomb hollow core door with lock slot. Painted WP03.</p> <p>IRONMONGERY: Hinges: 3x IRONWARE IW 3040 100x44mm Sinkless Hinge. Handle Set: IronWare – IW Calini 1019 through fix Lever Handle (Brushed Stainless Steel). Escutcheon: IronWare – IW Calini 1904-24SS screw type Rose (Brushed Stainless Steel). Lock Set: Dorma D036S Multi Lever Sash Lock. Door Stop: IronWare – IW 5000 Cylindrical door stop (SS).</p>	
<h1>TYPE [G-01]</h1> <h2>0.8M X 2.1M GLASS LIGHT</h2>	
<p>Standard Height glass light (800 x 2066)</p>	
FRAME [G-01]	
PLAN VIEW [G-01]	
DESCRIPTION 'G-01'	
<p>FRAME: 800mm wide by 1966mm high Aluminium frame with 20mm wide frame edge and 10.38mm glass catch rubber section to suit 90mm thick dry-walling system. Clear open section for glass panel = 760mm wide x 1926mm high. All rubber Dove Grey in colour (No Black).</p> <p>GLASS: Ordered to suit 760mm wide x 1926mm high open section. All edges to be polished. Glass to be from 6.4mm Laminated Safety Glass or better if required by NBR and comply with SANS 1263-1 and bear NRCS approved mark.</p> <p>LAMINATE: See Signage Schedule: INT-TYPE-02; and Signage Laminate Cutout.</p>	

[illegible]